MICROCOMPUTER DESIGN FOR
ELECTRONIC EMITTER IDENTIFICATION

Gary Lew Bush

NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

MICROCOMPUTER DESIGN FOR

ELECTRONIC EMITTER IDENTIFICATION

by

Gary Lew Bush

September 1979

Thesis Advisor: Frank Burkhead

Approved for public release; distribution unlimited

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Microcomputer Design for Electronic Emitter Identification		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis; Sept. 79
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Gary Lew Bush		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		12. REPORT DATE September 1979
		13. NUMBER OF PAGES 61
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office) Naval Postgraduate School Monterey, California 93940		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

table look-up
no degradation
off-line

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

New technological advances in weapons and electronics has increased the fighting capabilities of small ships. The increases are seen in better and lighter offensive weapons, along with, increases in self-defensive weapons through the addition of electronic suites. The electronic warfare suites currently used on small ships are limited in size, weight,

DD $\frac{\text{FORM}}{\text{1 JAN 73}}$ 1473　EDITION OF 1 NOV 68 IS OBSOLETE
(Page 1)　S/N 0102-014-6601 |

and response time because of the environment in which
these ships are employed. It is the purpose of this
paper tp propose a system which will allow the
currently very limited data bases to expanded while
at the same time not degrading the system. The
feasibility of this approach is based upon using a
microcomputer to aid in the identification of emitters
off-line while leaving the current system to identify
high threat emitters.

MICROCOMPUTER DESIGN FOR

ELECTRONIC EMITTER IDENTIFICATION

by

Gary Lew Bush
Lieutenant, United States Navy
B.B.A., North Texas State University, 1974

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN COMPUTER SCIENCE

from the

NAVAL POSTGRADUATE SCHOOL
September 1979

ABSTRACT

New technological advances in weapons and electronics
has increased the fighting capabilities of small ships. The
increases are seen in better and lighter offensive weap-
ons, along with, increases in self-defensive weapons through
the addition of electronic suites. The electronic warfare
suites currently used on small ships are limited in size,
weight, and response time because of the environment in
which these ships are employed. It is the purpose of this
paper to propose a system which will allow the currently
very limited data bases to be expanded while at the same
time not degrading the system. The feasibility of this
approach is based upon using a microcomputer to aid in the
identification of emitters off-line while leaving the
current system to identify high threat emitters.

TABLE OF CONTENTS

I. INTRODUCTION

The loss of the Israeli destroyer Eilant to the Egyptian fast patrol boat, during the October War, demonstrated the use of new technology in offensive weaponry. This demonstration paved the way for new interest in the investment of electronic warfare equipment. The interest took the form of electronic suite additions to ships that, up to now, had previously done without. It also manifested itself through improvement in the larger ships by doing away with the World War II type electronic surveillance measures (ESM) and electronic countermeasures (ECM). In their place came new, highly sophisticated, computer controlled systems.

The ECM capabilities were designed to help degrade the effectiviness of the opposing forces weapons, however, the best defense that a ship has is to avoid detection in the first place. One action to take, to meet this objective, is to turn off all active electronic devices which can give away the ship's presence. Add to this action the passive exploitation of electronic emissions from the opposing forces and you have a very effective way of avoiding detection while allowing the ship to maneuver into position for attack. Sounds good, however, there is a drawback.

The drawback is that the only way to identify electronic emissions is through their parameters. These

parameters are contained in the Electronic Order of Battle (EOB) files which today consists of approximately 14,000 known land sites with a total of 62,000 emitters; 1,200 types of commerical and combatant aircraft; 28,000 commercial and combatant surface ships; 1,100 submarines and 350 different missile systems.[1]

The current electronic warfare (EW) systems presently contain between 75 and 500 emitters in their libraries, therefore, it is quite possible that a majority of the emitters intercepted are not going to be in the system library. The commanding officers of these ships will have two options left open to them. One, remain silent in the hope that the other contact will not detect him, or two, activate active electronic devices in order to try and establish the identity of the contact. The second choice defeats the best defensive weapon the ship has and should be used only as a last resort.

II. BACKGROUND

A. SOVIET INTEREST IN ELECTRONIC WARFARE

The Soviets have for many years recognized the impor-
tance of electronic warfare in all aspects of military
operations. In his book Soviet Military Strategy, Marshall
V.D. Sokolovski summarized the role of electronic warfare in
Soviet strategy by first identifying the dual mission of EW,
namely denial and protection.

He continued: "Merely to list the uses of electronic
warfare is to show how widespread are electronic counter-
measures(ECM) and defense against electronic countermeasures
and how serious the consequences can be. For this reason the
development of electronics has now acquired the same impor-
tance as the development of missiles and nuclear weapons
which cannot be used without electronic equipment." He thus
also identified the electronic warfare/general warfare
balance in modern warfare. The former first deputy minister
of defense wrote this in the 1960's. Later in that decade
the Soviets engaged in EW activity in a way which surprised
many Western military observers. The operation, now a
classic in EW history, was the large-scale invasion of
Czechoslovakia in August 1968.

The Soviets made extensive use of ECM in the form of active jamming, together with a blanket of chaff under the cover of which they assembled and transported Soviet forces in airborne and ground units into Prague and other cities without alerting NATO forces. Soviet military doctrine dictates the use of large troop formations, a situation which makes deception difficult and thus the use of noise jamming and chaff is most appropriate. Since 1968, Warsaw Pact forces have reportedly made considerable investments in electronic warfare, with particular emphasis on training.[2]

B. PASSIVE WARFARE

Passive warfare includes a mixture of elements of EW and other passive sensors with hard kill weapon response suites. It includes the use of passive techniques, methods, equipment and training for detection (including identification, classification, and track), control (threat evaluation, weapon selection, and assignment) and engagement (target acquisition through target kill) of enemy targets. Increased interest in passive warfare was stimulated by the development of long range autonomous missiles that are capable of seeking out and destroying enemy shipping beyond the radar horizon.

Passive warfare has not gained general acceptance as a mode of naval warfare. The paucity of available data and

experience with passive techniques in operational situations hinders expansion of the theoretical concepts. Operators engage in few exercises utilizing passive techniques common to other areas of warfare but return to traditional classical methods of employing active sensors in responding to potential threats. Differences of opinion in the military worth of passive techniques and response systems among various established groups typified by the hard-kill weapon advocates and so called active EW "electron gun" enthusiasts continue to hinder the expansion and acceptance of passive warfare. Its role in respect to other modes of warfare and the needs of the total force must be resolved to counter the sophisticated threat in modern warfare.

The dependence on high-technology weapon systems which rely primarily on active sensors (e.g. radar) that uses some region of the electromagnetic spectrum for control and guidance information indicates the need for further attention of naval planners to seek the optimum mix of ESM/ECM/ECCM (electronic counter countermeasure) and weapons. No longer can fleet units continue to freely broadcast their positions to the enemy and survive. More attention to rigorous control of onboard active devices is needed along with disciplined operations which include consideration of both active and passive capabilities. The time has come to expand passive warfare and determine its role and contribution to naval warfare.[3]

C. SPECIAL PROBLEMS OF FAST PATROL BOATS

Fast patrol boats (FPBs) are not without problems, however. They are vulnerable to anti-ship, and even aircraft, missiles. A 30mm-equipped aircraft gunship can destroy a FPB in a matter of seconds. Sea skimmers are especially effective against FPBs. Payload and cost considerations do not often allow a highly effective AAA or SAM system to be placed onboard, except in the very largest FPBs such as the Soviet Nanuckla-class ships. Five-inch and larger naval guns or shore batteries have FPBs at a disadvantage if they venture too close to their intended targets or are slightly careless with their navigation. Missile carrying FPBs cannot afford to engage in duals with platforms other than their intended targets because of their limited supply of offensive weapons. The cost of FPBs is low, but only relatively speaking. To most users, the cost is not low enough to allow truly massive FPB attacks which would overwhelm enemy defenses without regard to the FPB losses. Some sort of protection is needed. Finally, a typical FPB cannot reload at sea. The first shots must be accurate and be directed at the target intended. There is essentially no "second chance." Expending ammunition and missiles for self-defense, at spurious targets, or engaging non-hostiles requires a high degree of pre-launch confidence in target identification and location. The use of the FPB's radar does

not often give a high level of confidence that the inter-
cepted entity is truly the target desired. The use of
electronic warfare assets will largely overcome these
problem areas.[4]

D. THE COMPUTER IN ELECTRONIC WARFARE

A central computer forms the nucleus of the system where
the high level processing is performed and from which the
executive commands would emanate. Remotely located
microprocessors would be dedicated to performing the low
level, routine tasks associated with real-time,
hardware-related functions. ECM techniques are sufficiently
flexible to allow new techniques to be implemented via
software modifications rather than costly and time consuming
hardware changes.[5]

The AN/SLQ-29, AN/SLQ-32, AN/SLR-21 and EW-130 series
are some of the current systems using computer technology.
The AN/SLQ-29 is used onboard large ships such as aircraft
carriers. The AN/SLQ-32 is used onboard smaller ships such
as DDG, FFG and small auxiliaries. The AN/SLR-21 and EW-100
series are used on FPBs.

III. ELECTRONIC WARFARE AND EQUIPMENT REQUIREMENTS

A. ELECTRONIC WARFARE REQUIREMENTS

1. Performance

The basis for performance requirements lies in the primary functions of the system. In the case of the AN/SLQ-32 and similar systems, the following items are of prime concern. First, surveillance which is the monitoring of the electromagnetic environment in the radio frequency bands (normally between 8 - 18 GHz) and over angular regions where hostile emitters can be expected. Secondly, the identification of an emitter is done by comparing its characteristics with those of known emitters. Third, warning which means to monitor the environment and provide a warning whenever a change occurs; for example, detection of a new emitter or change in an operational mode of an old emitter. Fourth, countermeasures are measures that are taken in the event that a new emitter has been identified as hostile and initiates countermeasures which will degrade the performance of the hostile emitter/platform. Fifth, operator/system interaction which provides controls allowing the operator to initiate or modify system operation on the basis of the situation. Finally, intersystem interaction which interfaces with other onboard systems and exchanges information as

required in order to maximize the survivability of own ship and to facilitate the deployment of other weapons.[5]

2. Operational

The basis for operational requirements lies in the following items. First, the environment which affects the ship while conducting offensive strike warfare in support of carriers or other task forces, such as underway replenishment and military convoys. Success in these strike operations, especially those operations without air support, depends upon continuous shipboard surveillance to provide target information for quick response to anti-ship missile attacks. Ideally, our ships will remain undetected while conducting extended-range surveillance with a high probability of initial detection and identification of enemy ships. Secondly, the tactics used are normally those of passive-offensive capability in which complete radar silence is maintained while utilizing rapid and reliable covert telecommunications to disseminate passive targeting data and engagement control orders.[3]

3. Special Applications

The special requirements of certain ships add additional concerns with respect to ship functions. They are as follows. First, in the case of fast patrol boats (FPBs),

their requirements for warning and acquisition receivers are not very much different from presently available electronic surveillance measurement systems. A few exceptions exist, however, in addition to the restrictions on size, weight, reliability and ease of operation. The last item is important because the level of competence available for operations of the electronic warfare system may likely be quite low. Secondly, the frequency coverage should be, as a minimum, between 8 - 18 GHz, which is the frequency range in which most threats are expected to be found presently and into the near future. Third, sensitivity, because of the need for intercept of targets and threats beyond their maximum detection range, should be better than usual crystal video receivers. In addition, relatively low mast heights on a fast patrol boat require additional sensitivity. However, increased sensitivity requires increased complexity -- a highly weighted factor on FPBs. Fourth, azimuth coverage of 360 degrees would, of course, be required and elevation coverage should cover from 0 degrees (to intercept sea skimmers) to a minimum of +30 degrees. A stabilized platform with +45 degrees azimuth coverage would be much preferred. The severe pitch and roll of FPBs help create the need for stabilized antennas. Finally, a programmable threat library would be mandatory in an FPB electronic surveillance measure suite, so that it could remain small and be loaded in at the pier for the mission, the scenario expected and the operations planned.[4]

4. Meeting of Requirements

Current systems like the AN/SLQ-32 and AN/SLR-21 systems meets most of the hardware requirements but fall short when it comes to the functional and operational requirements. The shortcomings are due to the size, weight and response time constraints on small ships. However, even if the size and weight constraints could be lifted to handle larger systems, the response times of those systems would also increase, which in critical cases such as missiles, would not be acceptable. Therefore, by adding a micro-computer system off-line, there would be no degradation in the current systems. The addition of this system will, however, allow identification of emitters well beyond the limited libraries of those systems and at the same time change what was a previously data base limited system to one bound only by the decision of the operator to cease search.

B. EQUIPMENT REQUIREMENTS

1. Memory Size

The memory size of the prospective off-line micro-computer would be 48k bytes minimum. The allowance would include 4k bytes for the operating system, 12k bytes for the processing programs, and 32k bytes for library array

processing. The system should also allow a growth factor of approximately 33%, bringing the preferred memory size to 64k bytes. Most microcomputers currently have this capacity option as an off-the-shelf item and would not require any special design changes.

2. Disk Drives

The major constrainting factor of the prospective system lies in the disk drives currently available as an off-the-shelf item. The constraint takes the form of head dimensions and densities of the disk drives. The prospective system is based upon the use of an IBM 3740 style floppy disk with 77 tracks per disk, 26 sectors per track, 128 bytes per sector, and single density.

3. Electronic Emission Control

The prospective system will have to be capable of operating under electronic emission control (EMCON) conditions. It would, therefore, be necessary for the system to conform to the MIL-STD-461 for TEMPEST inspection. The requirement can be meet with current systems on the market.

IV. COMPUTER APPLICATION

A. SEARCH PROBLEM

A basic requirement appearing in many data-processing
problems is the need to search a mass of information for
certain information associated with specific information   on
hand. We begin with some terminology and symbol definitions
for an abstract statement of a search problem.

F   Denotes a file, here considered as a matrix.

F[I;]   Denotes a record ´I´ of the file (also
           called an item ´I´).

F[;J]   Denotes a position ´J´ of all records of the
           file. F[;J] is a column vector of ´F´.

X   Denotes an argument to be used on the basis
           of search. ´X´ will usually correspond to
           a part of a record and is considered a
           vector.

M   Denotes a mask or format vector which speci-
           fies, by its elements, which columns of ´F´
           are to participate in the search.

With the above terminology, a simple but common search
problem may be stated in words as: Given a file ´F´, a
format vector ´M´, and an argument ´X´. Find ´G´, a sub-
matrix of ´F´ containing all those records of ´F´ whose
contents in the key positions match the argument.[6]

The file used here is made up of a set of records (128
bytes long) in the following format:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16

1. Radio Frequency Low   (RFL)
2. Radio Frequency High   (RFH)
3. Pulse-repetition Frequency Low   (PRFL)
4. Pulse-repetition Frequency High   (PRFH)
5. Scan Period Low   (SPL)
6. Scan Period High   (SPH)
7. Scan Type   (ST)
8. Pulse Width Low   (PWL)
9. Pulse Width High   (PWH)
10. Modulation Type
11. Elint Notation
12. Mode Counter   (MC)
13. NATO Nickname
14. Emitter Function Code (FC)
15. CDS Number   (Formally NTDS)
16. Comments

The file record is made up of file items (F[I;]) such as
RFL, RFH, PRFL, etc. The file column vector (F[;J]) contains
all RFLs, or all RFHs, etc., on one disk. The file is limit-
ed to 1950 records per disk, but the number of disks is not
limited. Therfore, the data base is no longer limited by
memory size constraints.

The argument vector 'X' is composed of radio frequency
(RF), pulse-repetition frequency (PRF), scan and scan type.
It is entered into the system by the operator which has read
it directly from the display of the current system such as
the AN/SLQ-32.

The mask vector is comprised of RFL, RFH, PRFL, PRFH,
SPL, SPH and ST. The remainder of the file is used for the
output information to the operator when the search is
successful. As noted, the items of the argument are specific

while the items in the mask are specific only in the scan type. The other items are the upper and lower limits of the argument items and are satisfied only when the argurment items lies within these limits.

B. COMPARISON OF SEARCH ALGORITHMS

The three basic search algorithms are sequential, hashing, and binary. The normal approach is to apply only one of them at a time, however, a combination of them may be used if the situation warrants. In the case of the micro-computer, a very limited memory size and the desire to maximize the number of records on the disk required keeping pointers to a minimum. It also required the file to be broken up into partitions consisting of 250 records each, which allows one partition to fit into the machine memory at any one time. Putting these records into memory vice leaving them on the disk will benefit the system by cutting down on the number of accesses to the disk while increasing the speed of the search.

In the interest of minimizing the accesses to the disk, which takes a longer time in comparison to accessing memory, a reference table was added to the disk holding the ad-dresses of all partitions and the maximum and minimum values of the RF which is the primary search key. With this

in mind, only those partitions which satisfy the RF item in the argument will be eligible for loading into memory.

The comparisons of the search methods will be based upon the aforementioned and their particuliar circumstance. The common terms for the comparison are as follows:

Let A = Machine time to do one comparison.

B = Total access time of disk (including the transfer of 1 segment).

C = Time to load and process the reference table from the disk.

P = Number of partitions (max. of 8).

N = Maximum partition size (250 records).

I = Number of items in the argument.

Assumption: Only one partition needed per search.

The worst case for the sequential search method is where the record that satisfies the argument is located at the bottom of the file.

$$
\begin{aligned}
\text{Total Time} &= P([N * I * A] + B) + C \\
&= 1([250 * 4 * A] + B) + C \\
&= 1000A + B + C
\end{aligned}
$$

The hashing search method is based upon a value derived from an argument vector. In this application, the argument key is already in the form of a value which lies between two

limits. Because the hashing value is unique, it is not applicible to this situation.

The worst case for the binary search method is where the record that satisfies the argument lies either side of the mid point, or is the second record in the file or is the next to last record in the file. Mathematically it is $\log_2 N$. Its proof is to consider the binary decision tree describing the action of a binary search on n elements. All successful searches end at a node while all unsuccessful searches end at a leaf. If $2^{k-1} < n < 2^k$ (k is the number of levels in the tree) then all nodes are at the levels 1,2,----k, while all leaves are at levels k and k+1 (note that the root node is at level 1). The number of element comparisons needed to terminate at a node on level i is i while the number of element comparisons to terminate at a leaf at level i is only i-1.[7] The following equation shows the total time of the search based upon that only three of the four items in the argument can be used in a search of this manner. The fourth will be searched sequentially.

Let S = I-1

Total Time = P(S[$\log_2$ N] * A - B) + C + (N * A)
= 1(3[8] *2 A + B) - C + (250 * A)
= 24A + B + C + 250A
= 274A - B - C

Note: (N * A) is the sequential search of the
fourth item.

Based upon the comparison of 274 to 1000, the binary search with the modifications stated was chosen for this application.

C. NEED FOR SORTING

The use of a sequential search does not require that the file be in any particular order. However, in the case of the binary search, it is mandatory that the file be in either increasing or decreasing order because the binary search is based upon the idea that after one comparison; half of the file can be eliminated followed by a repeat of the technique on the remaining half until the search is completed. The sorting scheme used in this application was to place the file into an increasing order. There are, in this case, three fields that must be in increasing order. They are RF, PRF, and scan.

The process used was to take a partition of the file and only load the RFL, RFH, PRFL, PRFH, SPL, and SPH mask vectors into memory. During this load, each record is assigned a record number in increasing order. The next process was to divide the partition into a subset with all the same RFLs, after a bubble sort on the RFLs. Next, perform a bubble sort on all RFHs followed by dividing this vector in a subset of the subset containing all of the PFHs with the same value. The process is repeated for the

remaining items PRFL, PRFH, SPL, and SPH. Once the first
pass is made on the final subset, the process is back
stepped one iteration and done again. The process is
continued until the entire file is sorted. For more details
on the process, see the PROCEDURE SORT in APPENDIX B.

At the conclusion of the sort, the modified file will be
in increasing order in all fields except the record number.
It will be in disorder but in the order in which the file
will have to be converted to place it into increasing order.
To do this, the record number is saved in an array and used
to reference each record number in the partition. The
process then is to load memory with the partition in the
order of the saved array, followed by rewriting the
partition on the disk. Once this is done, the partition will
be in increasing order and there will be no futher need for
modifications.

D. DISK FILE STRUCTURE

The disk contains a directory on track one. The
directory contains pointers to seven segments containing 250
records each, one segment with 200 records, and a reference
table. The reference table is made up of the maximum and
minimum RF values of each segment and the minimum and
maximum RF value for the disk. It is this table that points
to what segment or segments will be loaded into memory.

The logical arrangement of the disk is as follows:

DISK

DIRECTORY

| SEG 1 | ----------------- | SEG 8 | REF. TABLE |

	RF		
	MAX	MIN	SIZE
DISK	.	.	—
SEG 1	.	.	.
.	.	.	.
.	.	.	.
SEG 8	.	.	.

250 RECORDS
(128 BYTES
EACH)

200 RECORDS
(128 BYTES
EACH)

The disk is not supplied in the proper format because it
would mean that the support facility would have to access
all of the different kinds of equipment that are in the
fleet. It is not necessary for the support facility to have
all of the equipment involved if it can produce the data in
a standard format and on standard media. It can later be
modified by the user's software to conform to any special
needs of the user.

The reformatting program PROCEDURE REMAT can be seen in
the APPENDIX B. The program reads 512 bytes of source data
of which only 128 bytes (due to the dissimilarity between
operating systems) is written into the segment at any one

time. The order of writing is first into segment one, then
when 250 records have been written, it writes segment two
and so on until all records are written onto the disk.

The restrictions of using track one thru seventy-six,
the reading of 512 byte blocks, and limiting the arrays to a
maximum of 16k words are imposed by the UCSD PASCAL sys-
tem.[8] It is these restrictions that prompted the breaking
up of the source file into eight segments. Another
restriction was the format of the disk which makes best use
of 128 byte records.

The support facility's record size is compatible but of
different arrangement than what would be necessary for
efficiency in this application and was therefore changed.
The first two diagrams represent how the data is received
and the third diagram is how it is reformatted into an
efficient form for this program.

IDENTIFICATION RECORD

| 1 | 2 | 3 | 4 | 5 | 6 |

1. Elint Notation   0-4
2. Mode Counter   7
3. NATO Nickname   9-20
4. Emitter Function Code   22-23
5. Four Digit CDS Number   26-29
6. Comments   37-60

27

PARAMETER RECORD

1	2	3	4	5	6	7	8	9	10	11	12	13

1.	Elint Notation	0-4
2.	End Mode	5
3.	Mode Counter	6-7
4.	RF Low	9-13
5.	RF High	15-19
6.	PRF Low	21-25
7.	PRF High	27-31
8.	Pulse Width Low	33-36
9.	Pulse Width High	38-41
10.	Modulation Type	44
11.	Scan Type	46-50
12.	Scan Period Low	52-55
13.	Scan Period High	57-60

REFORMATTED RECORD DESIGN

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16

1.	RFL	0-4
2.	RFH	6-10
3.	PRFL	12-16
4.	PRFH	18-22
5.	SPL	24-27
6.	SPH	29-32
7.	ST	35-39
8.	Pulse Width Low	41-44
9.	Pulse Width High	46-49
10.	Modulation Type	51
11.	Elint Notation	64-68
12.	Mode Counter	70
13.	NATO Nickname	72-84
14.	Emitter Function Code	85-86
15.	CDS Number	88-91
16.	Comments	92-116

E. TRAINING

The capabilities required of the operator is that he be able to read and follow some simple instructions. He will also be required to enter information into the system from the display unit of the current detection equipment, such as an AN/SLQ-32. No other special skills will be required of

him; therefore, he will not have to have any training off of the ship.

F. OTHER APPLICATIONS

The proposed system should be used as a dedicated system to help identify electronic emitters while at sea. However, when inport there are areas where the microcomputer could be used to lighten the burden of administration. Some of these areas are in the reports and reporting fields. Godley [10], while at the Naval Postgraduate School, commented on how a microcomputer could be used in recurring operational reports and how this would benefit the Navy. Text processors are also commercially available for microcomputers and they too would help in formatting letters and messages. It then is up to the respective commanding officer to determine just how much a microcomputer can help his command.

V. COST AND SUPPORT

The basic system is comprized of a terminal (consisting of a video screen and keyboard), a microcomputer of the 8080 or Z80 design with 64k of memory, and dual 8" floppy disk drives. The approximate cost of the system is as follows:

Terminal		$1000
Microcomputer with drives		$4000
	TOTAL	$5000

As an option, a printer can be added to the basic system for inport use. The system can be purchased by the type commander or, according to a new regulation, by the commanding officers of their respective ships because the system's cost is less than $10,000.

The data base support would be from Naval Electronic Evaluation Office, Damneck, Virgina. Contact should be made with them prior to any purchase of any equipment to verify their requirements for continued support.

VI. PROGRAM IMPROVEMENTS AND FUTURE CONSIDERATIONS

A. PROGRAM IMPROVEMENTS

The two currently available operating systems CPM and UCSD PASCAL were the driving forces behind their selection for this project. However, with new operating systems continually being developed the reformatting software program was built with the idea of flexibility. It can be modified to read any sector on the disk and transcribe it into the correct format needed for processing under the available programs. Studying the reformatting program closely will reveal that if the operating system is using a directory listing on any track (except track one) the listing can be pulled off. Then by developing an equation to decode this information all sectors can be pulled off in the correct order.

The only thing to check is that the initial data stored on the disk, supplied by the support facility, is the same as the data described eariler in this paper. Given that it is, the only constraining factor is the hardware. The hardware constraint is that the disk be of the type IBM 3740 style floppy disk with 77 tracks per disk, 26 sectors per track, 128 bytes per sector, and of single density.

The improvement of this program will come about through expansions due to decoding of new operating systems disk directories. It will also be necessary thru interactive communications with the low skilled operator to establish who supplied the disk, thereby establishing which equation to use in reformatting the input data. The process in which the reformatting is done should remain transparent to the operator. He should only have to respond to questions presented to him on the CRT and load the disk as directed.

B. FUTURE CONSIDERATIONS

1. Operating System Modifications

The normal typist will type approximately 30 to 60 (five letter) words per minute. Using the 60 word per minute as a norm, the time interval between characters of input then is two tenths of a second. Allowing for a 50% safety factor for keybounce, settling out of transient signals and various other static factors, leaves one tenth of a second that could be used for processing. Agreed that this does not sound like much time in the normal sense, to a computer with instruction times between 4 - 10 micro seconds this is 10,000 - 25,000 instructions that could have been done without any delays in the inputs from the keyboard.

With this in mind, a modfication to the operating system would increase the response time to the user without any degradation to the system. In addition, if a queueing scheme, which would allow stacking of request for processing, was included and implemented with a priority system, the over all system performance could be improved.

The consideration of the operating system modification would have to be based upon sound computer science studies. The field is open and presents a challenge to any student who is interested in applying this concept to a table look-up identification scheme.

2. Passive Plotting of Contacts

The biggest problem with plotting a contact through passive intercept is with the intermittent short signals. These signals do not allow the intercepting platform to get a cut on the signal and proceed to a distant point and again get another cut, thus allowing the position to be plotted.

Couple the system described in this paper and one that is currently being done on milliwave transmissions by Mark Schneider and Mike Chase at the Naval Postgraduate School and these imtermittent signals can be plotted. The way that it will work is that digital signals can be transmitted over these milliwaves in such a manner that unintentional dis-

closures of own ship's position is fairly unlikely. It will require that two ships which have the equipment are within sight of one another and each ship gets at least one cut on the intermittent signal, followed by a transmission over the milliwave system to establish the distance between the two ships through the same type of process now being used in most radars (a send and receive signal vs time). With the bearing cuts of each ship plus their distances apart at the time of intercept, a plot of the contact can be made.

APPENDIX A

USER'S PROGRAM GUIDE

The program was implemented on the ALTOS microcomputer system with a DATAMEDIA ELITE 2500 terminal. The booting and loading instructions for this system will be used for examples. However, if a different system is being used, the booting instructions may vary, so the operator's manual must be checked. Once the system is booted and the screen writes its welcome message, all other instructions will be the same.

Example 1: Booting

    Step 1.   Turn power on (it is located on the
              back of the microcomputer and on the
              right hand side of the CRT terminal).

    Step 2.   Place the disk labeled 'SYSTEM' into
              the right hand side of the drive with
              the label faced to the operator and
              down.

    Step 3.   Depress the key labeled D/2 if the
              full duplex lamp (located on front
              of the CRT terminal) is off.

    Step 4.   If the symbols '%*' are not on the
              screen depress the rest button located
              on back of the microcomputer.

    Step 5.   If the symbols '%*' are on the screen
              depress the key labeled LOCK and verify
              that it remains in the down position.

    Step 6.   Depress the key labeled 'U' followed by
              depressing the key labeled RETURN.

The system should be booted at this time. If the screen does not display the welcoming message repeat the steps two thru six. The welcoming message is as follows:

```
Command: E(dit, R(un, F(ile, C(ompile, H(alt.
WELCOME USER, TO
U.C.S.D. PASCAL SYSTEM I.xx
```

The next phase to complete is the loading instructions and they will be the same for all systems.

Example 2: Loading

    Step 1.   Depress the key labeled ´F´. The screen will display ´Filer: G(et, S(ave, W(hat, Q(uit´.

    Step 2.   Depress the key labeled ´G´. The screen will display ´Get what file?´.

    Step 3.   Depress the keys labeled ´I´, ´D´ and RETURN. The screen will display ´Text and code file loaded.´

    Step 4.   Depress the key labeled ´Q´. The screen will display ´Command: E(dit, R(un, F(ile, C(ompile´.

    Step 5.   Depress the key labeled ´R´. The screen will display ´WELCOME TO THE ELECTRONIC EMITTER IDENTIFIER´.

The booting and loading is now completed. The micro-computer will converse with the user through some simple instructions. In response to these instructions the user will be asked to make entries. These entries are of the form of answers to questions. If the user is asked for (Y/N) this means for him to depress the key labeled ´Y´ for yes or the

key labeled 'N' for no. In any other response, the response will be followed by depressing the key labeled RETURN. The statments requesting this type of response will have <rtn> attached to them, such as PRF(xxxxx) <rtn>. In response to entries requiring number inputs such as PRF(xxxxx) <rtn>, the x's represent numeric numbers and the entry should contain only numbers. In the case of SCAN TYPE (AAAA), the response must be alpha characters and in the same amount that is enclosed in the parenthesis (). If the scan type display on the electronic detection equipment has less then that shown in the parenthesis, spaces made be added to the leading character, such as CON the entry would be <space>CON. The final case, is where the user is asked if he wants to change any parameters. An example of this type follows:

```
YOUR ENTRIES ARE:

   PRF         RF          SCAN        SCAN TYPE
  00005       01035       00020          CON

DO YOU WANT TO CHANGE ANY?  (Y/N)   Y

WHICH ONE DO YOU WANT TO CHANGE (PRF,RF,SCAN,SCAN TYPE) <rtn>
SCAN TYPE

ENTER SCAN TYPE (AAAA) <rtn> SWEP

YOUR ENTRIES ARE:

   PRF         RF          SCAN        SCAN TYPE
  00005       01035       00020          SWEP

DO YOU WANT TO CHANGE ANY? (Y/N)   N
```

PROGRAM DOCUMENTATION

A. PROCEDURE REMAT

```
PROCEDURE REMAT;
VAR BLOCKNR, LENGTH, UNITNR: INTEGER;
    TRACK, SETOFF, SECONR:   INTEGER;
    SEGCNT, CPMSEC, CNT, LINE: INTEGER;
    TABLE, DFILE: TEXT;
    SEGMEY: STRING[11];
    CPMARAY: PACKED ARRAY[0..511] OF CHAR;

FUNCTION CPM(SECTOR:INTEGER): INTEGER;
BEGIN
 SECTOR := SECTOR + 6;
 IF SECTOR < 26 THEN CPM := SECTOR
  ELSE
    BEGIN
     IF SECTOR <> 27 THEN
      BEGIN
        SECTOR := SECTOR MOD 26;
        IF SECTOR = 0 THEN SECTOR := 1;
        CPM := SECTOR;
      END
     ELSE
       CPM := 0;
    END;
END;

FUNCTION OFF(CPMSEC,SECTOR:INTEGER): INTEGER;
VAR OFFSET, STRSEC: INTEGER;
 BEGIN
  OFFSET := 0;
  IF SECTOR = 0 THE STRSEC := 24
   ELSE
    STRSEC := SECTOR - 2;
  WHILE SECTOR <> CPMSEC DO
   BEGIN
    OFFSET := OFFSET + 1;
    SECTOR := SECTOR + 1;
    IF SECTOR >= 26 THEN SECTOR := SECTOR MOD 26;
    IF (SECTOR = STRSEC) AND (SECTOR <> CPMSEC)
     THEN SECTOR := STRSEC - 1;
    IF OFFSET > 3 THEN
     BEGIN
      OFFSET := 0;
      BLOCKNR := BLOCKNR + 1;
     END;
   END;
```

```pascal
    ODD := OFFSET;
  END;

FUNCTION EVEN CPMSEC,SECTOR:INTEGER): INTEGER;
VAR OFFSET, STRSEC: INTEGER;
  BEGIN
   OFFSET := 2;
   IF SECTOR = 0 THEN STRSEC := 24
    ELSE
     STRSEC := SECTOR - 2;
   WHILE SECTOR <> CPMSEC DO
    BEGIN
     OFFSET := OFFSET + 1;
     SECTOR := SECTOR + 1;
     IF SECTOR >= 26 THE SECTOR := SECTOR MOD 26;
     IF (SECTOR = STRSEC) AND (SECTOR <> CPMSEC)
      THEN SECTOR := STRSEC - 1;
     IF OFFSET > 3 THEN
      BEGIN
       OFFSET := 0;
       BLOCKNR := BLOCKNR + 1;
      END;
    END;
  EVEN := OFFSET;
END;

PROCEDURE PAGE1;
BEGIN
 BLKPAGE;
 WRITELN('PLACE DISK LABELED SUPPORT FACILITY');
 WRITELN('INTO THE LEFT SIDE DISK DRIVE WITH THE');
 WRITELN('LABEL FACING YOU AND DOWN');
 WRITELN;
 WRITELN('REMOVE THE DISK LABELED SYSTEM FROM THE');
 WRITELN('RIGHT SIDE DISK DRIVE AND SAVE FOR REUSE.');
 WRITELN;
 WRITELN('PLACE A BLANK DISK INTO THE RIGHT SIDE DISK');
 WRITELN('DRIVE WITH THE LABEL FACING YOU AND DOWN');
 WRITELN;
 WRITELN;
 WRITELN('HAVE YOU COMPLETED THIS AND ARE BOTH DISK');
 WRITELN('DRIVE DOORS CLOSED?  (Y/N)');
 READ(C);
 WHILE C <> 'Y' DO
   READ(C);
 BLKPAGE;
 WRITELN('WORKING');
END;

PROCEDURE PAGE2;
BEGIN
 BLKPAGE;
 WRITELN('COMPLETED');
 WRITELN;
```

```
WRITELN('REMOVE DISK FROM LEFT SIDE DRIVE AND STORE.');
WRITELN;
WRITELN('REMOVE DISK FROM RIGHT SIDE DRIVE AND PLACE');
WRITELN('INTO LEFT SIDE DISK DRIVE.');
WRITELN;
WRITELN('PLACE DISK LABELED SYSTEM INTO THE RIGHT ');
WRITELN('SIDE DISK DRIVE WITH LABEL FACING YOU AND DOWN.');
WRITELN;
WRITELN;
WRITELN('HAVE YOU COMPLETED THIS AND ARE BOTH DISK');
WRITELN(' DRVIE DOORS CLOSED?   (Y/N)');
READ(C);
WHILE C <> 'Y' DO
READ(C);
BLKPAGE;
END;

PROCEDURE BUILD(CNT:INTEGER);
VAR I,J: INTEGER;

 PROCEDURE RF X,Y:INTEGER)
  BEGIN
   WHILE X < 24 DO
    BEGIN
     WRITE(DFILE. CPMARAY[Y];
     Y := Y + 1;
     X := X + 1;
    END;
  END;

 PROCEDURE SP(X,Y: INTEGER);
  BEGIN
   WHILE X 18 DO
    BEGIN
     WRITE(DFILE. CPMARAY[Y];
     Y := Y + 1;
     X := X + 1;
    END;
  END;

   PROCEDURE ST(X,Y: INTEGER);
    BEGIN
     WHILE X < 6 DO
      BEGIN
       WRITE(DFILE. CPMARAY[Y];
       Y := Y + 1;
       X := X + 1;
      END;
    END;

   PROCEDURE PW(X,Y: INTEGER);
    BEGIN
     WHILE Y < 62 DO
      BEGIN
```

47

```
            WRITE(DFILE, CPMARAY[Y];
            Y := Y + 1;
            X := X + 1;
          END;
        END;

   BEGIN (* BUILD *)
     I := 0;
     IF LINE < 252 THEN
       BEGIN
        J := CNT + 73;
        RF(I,J);
        J := CNT + 116;
        SP'I,J);
        J := CNT - 110;
        ST(I,J);
        J := CNT + 97;
        SP(I,J);
        WRITE DFILE, CPMARAY[126]);
        WHILE I < 11 DO
          BEGIN
           WRITE(DFILE,' ');
           I := I + 1;
          END
        WRITELN DFILE);
        I := 0;
        J := CNT;
        PW(I,J);
        WRITELN(DFILE);
        LINE := LINE + 1;
       END
     ELSE
       BEGIN
        CLOSE(DFILE.LOCK);
        WRITELN(TABLE,LINE);
        SEGCNT := SEGCNT + 1;
        CASE SEGCNT OF
         2: SEGMEY := 'SEG2.TEXT';
         3: SEGMEY := 'SEG3.TEXT';
         4: SEGMEY := 'SEG4.TEXT';
         5: SEGMEY := 'SEG5.TEXT';
         6: SEGMEY := 'SEG6.TEXT';
         7: SEGMEY := 'SEG7.TEXT';
         8: SEGMEY := 'SEG8.TEXT';
        END;
        REWRITE(DFILE, SEGMEY);
        LINE := 0;
        BUILD(CNT);
       END;
    END; (* END BUILD *)

  BEGIN (* FEMAT *)
   REWRITE(DFILE, 'SEG1.TEXT');
   REWRITE TABLE, 'REFTAB.TEXT');
```

41

```
CPMSEC := 19;
TRACK := 2;
UNITNR := 5;
LENGTH := 512;
LINE := 0;
SEGCNT := 1;
WHILE (NOT EOF) AND (TRACK < 76) DO
  BEGIN
   BLOCKNR := (TRACK - 1) * 65 DIV 10;
   SECONE := 0 + (TRACK - 1) * 6;
   IF SECONE >= 26 THE SECONE := SECONE MOD 26;
   IF ((TRACK - 1) * 65 DIV 10) = (((TRACK - 1)*65)+5) DIV 10
     THEN SETOFF := ODD(CPMSEC,SECONE)
      ELSE
        SETOFF := EVEN(CPMSEC,SECONE);
   UNITREAD(UNITNR, CPMARAY, LENGTH, BLOCKNR);
   CNT := SETOFF * 128;
   BUILD(CNT);
   CPMSEC := CPM(CPMSEC);
   IF CPMSEC = 0 THEN TRACK := TRACK + 1;
  END;
 CLOSE(TFILE, LOCK);
 WRITELN(TABLE,LINE);
 CLOSE(TABLE,LOCK);
END;
```

B.   PROCEDURE SORT


```
PROCEDURE SORT;
CONST     RFL = 0;
          RFH = 1;
         PRFL = 2;
         PRFH = 3;
          SPL = 4;
          SPH = 5;
         RECNR = 6;

VAR TABLE, DFILE : TEXT;
    SEGMEY: STRING[14];
    PTRTAB, SEGCNT, SIZE: INTEGER;
    POINT, TP, BP: INTEGER;
    RTAB: PACKED ARRAY[0..2,0..2] OF INTEGER;
    DTAB: PACKED ARRAY[0..249,0..6] OF INTEGER;
    CSEG: PACKED ARRAY[0..249,0..127] OF CHAR;
    DISKL, DISKH: INTEGER;

 PROCEDURE INREAD(BP:INTEGER);
 VAR I,J,K,L,M,N, PTR: INTEGER;
 BEGIN
  PTR := 0;
  WHILE PTR <= BP DO
  BEGIN
   READ(DFILE,I,J,K,L,M,N);
   READLN(DFILE);
   DTAB[PTR,RFL] := I;
   DTAB[PTR,RFH] := J;
   DTAB[PTR,PRFL] := K;
   DTAB[PTR,PRFH] := L;
   DTAB[PTR,SPL] := M;
   DTAB[PTR,SPH] := N;
   DTAB[PTR,RECNR] := PTR;
   PTR := PTR + 1;
   READLN(DFILE);
  END;
 END;

 PROCEDURE BUBBLE(TP,PARA:INTEGER);
 VAR I,TEMP:INTEGER;
 BEGIN
  WHILE TP < POINT DO
  BEGIN
   WHILE (DTAB[TP,PARA] <= DTAB[TP + 1,PARA])
   AND (TP < POINT) DO TP := TP + 1;
   IF TP < POINT THEN
   BEGIN
    I := 0;
    WHILE I <= RECNR DO
    BEGIN
     TEMP := DTAB[TP,I];
```

43

```
      DTAB[TP,I] := DTAB[TP + 1, I];
      DTAB[TP - 1,I] := TEMP;
      I := I + 1;
    END;
   END;
   IF (TP < POINT) AND (TP > 0) THEN
    TP := TP - 1;
  END;
END;

PROCEDURE UPDATF;
VAR I,J,K: INTEGER;
    A: CHAR;
BEGIN
 I := 0;
 WHILE I <= BP TO
 BEGIN
  RESET(DFILE);
  J := DTAB[I,RECNR];
  J := J * 2;
  K := 0;
  WHILE K < J DO
  BEGIN
   READLN(DFILE);
   K := K + 1;
  END;
  J := 0;
  WHILE J < 127 DO
  BEGIN
   READ(DFILE,A);
   CSFG[I,J] := A;
   J := J + 1;
  END;
  I := I + 1;
  READLN(DFILE);
 END;
 RESET(DFILE);
 I := 0;
 J := 0;
 WHILE I <= BP TO
 BEGIN
  WHILE J < 63 DO
  BEGIN
   WRITE(DFILE,CSFG[I,J]);
   J := J + 1;
  END;
  WRITELN(DFILE);
  WHILE J < 127 DO
  BEGIN
   WRITE(DFILE,CSFG[I,J]);
   J := J + 1;
  END;
  WRITELN(DFILE);
  J := 0;
```

44

```
  I := I + 1;
 END;
 CLOSE(DFILE,LOCK);
END;

PROCEDURE GROUP(PARA:INTEGER);
VAR I: INTEGER;
BEGIN
 I := TP;
 WHILE (DTAB[I,PARA] = DTAB[I + 1,PARA])
 AND ( I <= BP) DO I := I + 1;
 POINT := I;
END;

PROCEDURE TAB;
BEGIN
 RTAB[PTRTAB,0] := DTAB[0,RFL];
 RTAB[PTRTAB,1] := DTAB[BP,RFH];
 RTAB[PTRTAB,2] := SIZE;
 IF DISKL > DTAB[0,RFL] THEN
  DISKL := DTAB[0,RFL];
 IF DISKH < RTAB[BP,RFH] THEN
  DISKH := DTAB[BP,RFH];
 PTRTAB := PTRTAB + 1;
END;

PROCEDURE UPTAB;
VAR I,J: INTEGER;
BEGIN
 RESET(TABLE);
 WRITE(TABLE,DISKL,' ',DISKH,' ');
 WRITELN(TABLE);
 J := 0;
 IF (PTRTAB > 0) AND (PTRTAB < 9) THEN
 BEGIN
  WHILE J < PTRTAB DO
  BEGIN
   I := 0;
   WHILE I < 3 DO
   BEGIN
    WRITE(TABLE, RTAB[J,I],' ');
    I := I + 1;
   END;
   J := J + 1;
   WRITELN(TABLE);
  END;
 END;
 WRITELN(TABLE,'000  000  999');
 CLOSE(TABLE,LOCK);
END;

PROCEDURE ORDER;
BEGIN
 WHILE (TP < BP) AND (TP < POINT) DO
```

45

```
    BEGIN
     GROUP(RFL);
     IF TP < POINT THEN
     BEGIN
      BUBBLE(TP,RFH);
      GROUP(RFH);
      IF TP < POINT THEN
      BEGIN
       BUBBLE(TP,PRFL);
       GROUP(PRFL);
       IF TP < POINT THEN
       BEGIN
        BUBBLE(TP,PRFH);
        GROUP(PRFH);
        IF TP < POINT THEN
        BEGIN
         BUBBLE(TP,SPL);
         GROUP(SPL);
         IF TP < POINT THEN
         BEGIN
          BUBBLE(TP,SPH);
          TP := POINT;
         END
         ELSE
         TP := POINT;
        END
        ELSE
        TP := POINT;
       END;
       ELSE
       TP := POINT;
      END
      ELSE
      TP := POINT;
     END
     ELSE
     TP := POINT;
    END
   END;

BEGIN (* SORT *)
 RESET(TABLE,'REFTAB.TEXT');
 READ(TABLE,SIZE);
 READLN TABLE);
 SEGCNT := 0;
 IF (SIZE > 0) AND (SIZE < 250) THEN
  SEGCNT := SEGCNT + 1;
 ELSE
 BEGIN
  WRITELN('UNABLE TO PROCESS FILE.  CHECK DISK IN');
  WRITELN('LEFT SIDE DRIVE AND VERIFY THAT IT IS ');
  WRITELN('NOT LABELED SUPPORT FACILITY. ');
  WRITELN;
  WRITELN('PALCE THE DATA DISK IN THE LEFT SIDE DISK');
```

46

```
  WRITELN('DRIVE AND RELOAD. ');
  WRITELN;
  WRITELN('ARE YOU READY TO RELOAD?  (Y/N)');
  READ(C);
  WHILE C <> 'Y' DO
   READ(C);
  EXIT(SORT);
 END;
 BLKPAGE;
 WRITELN('WORKING');
 PTRTAB := 0;
 DISKL := 32726;
 DISKH := 0;
 WHILE SEGCNT < 9 DO
 BEGIN
  CASE SEGCNT OF
  1: SEGMEY := 'SEG1.TEXT';
  2: SEGMEY := 'SEG2.TEXT';
  3: SEGMEY := 'SEG3.TEXT';
  4: SEGMEY := 'SEG4.TEXT';
  5: SEGMEY := 'SEG5.TEXT';
  6: SEGMEY := 'SEG6.TEXT';
  7: SEGMEY := 'SEG7.TEXT';
  9: SEGMEY := 'SEG8.TEXT';
   END;
 RESET(DFILE,SEGMEY);
 BP := SIZE - 1;
 INREAD(BP);
 TP := 2;
 POINT := BP;
 BUBBLE(TP,FFL);
 WHILE TP < BP DO
 BEGIN
  ORDER;
 TP := TP - 1;
  POINT := BP;
 END;
 TAB;
 UPDATE;
 READ(TABLE,SIZE);
 READLN(TABLE);
 IF (SIZE >0) AND (SIZE < 9) THEN
  SEGCNT := SEGCNT - 1;
 ELSE
  SEGCNT := SEGCNT + 9;
 END;
 UPTAB;
END; (* SORT *)
```

47

C. PROCEDURE SEARCH

PROCEDURE SEARCH;

```pascal
TYPE ITEM = RECORD
                RFL: INTEGER;
                PFH: INTEGER;
               PRFL: INTEGER;
               PRFH: INTEGER;
                SPL: INTEGER;
                SPH: INTEGER;
                 ST: STRING[5]
              END;

VAR DFILE, TABLE: TEXT;
    DTAB: PACKED ARRAY[0..249] OF ITEM;
    FOUND, TP, BP, POINT: INTEGER;
    RF, PRF, SCAN, SIZE: INTEGER;
    SCANTYPE: STRING[5];
    KEEP: BOOLEAN;
    SEGMEY: STRING[14];

  PROCEDURE GROUPRF(I:INTEGER);
  BEGIN
   IF I > 0 THEN
   BEGIN
    WHILE (DTAB[I].RFL = DTAB[I-1].RFL) AND (I>TP) DO
     I := I - 1;
    TP := I;
   END
   ELSE
    TP := 0;
   IF I < 249 THEN
   BEGIN
    WHILE(DTAB[I].RFL = DTAB[I+1].RFL) AND (I<BP) DO
     I := I - 1;
    BP := I;
   END
   ELSE
    BP := 249;
  END;

  PROCEDURE GROUPPRF(I:INTEGER);
  BEGIN
   IF I > 0 THEN
   BEGIN
    WHILE(DTAB[I].PRFL = DTAB[I-1].PRFL) AND (I>TP) DO
     I := I - 1;
    TP := I;
   END
   ELSE
    TP := 0;
   IF I < 249 THEN
```

```
  BEGIN
    WHILE(DTAB[I].PRFL = DTAB[I+1].PRFL) AND (I<EP) DO
     I := I + 1;
   EP := I;
   END
  ELSE
   EP := 249;
END;

PROCEDURE GROUPSCAN(I:INTEGER);
BEGIN
 IF I > Ø THEN
 BEGIN
  WHILE(DTAB[I].SPL = DTAB[I-1].SPL) AND (I>TP) DO
   I := I -1;
   TP := I;
 END
 ELSE
  TP := Ø;
 IF I < 249
 BEGIN
  WHILE(DTAB[I].SPL = DTAB[I-1].SPL) AND (I<BP) DO
   I := I + 1;
   BP := I;
   END
 ELSE
  BP := 249;
END;

PROCEDURE FOND;
BEGIN
 BLKPAGE;
 WRITELN(' RF  PRT  SCAN  TYPE SCAN'):
 WRITELN(RF,'   ',PRT,'   ', SCAN,'   ',SCANTYPE);
 WRITELN;
 WRITELN('NOT FOUND'):
 WRITELN;
 WRITELN;
END;

PROCEDURE FOND;
VAR J,K:INTEGER;
BEGIN
 RESET(DFILE);
 J := FOUND * 2 + 1;
 K := Ø;
 WHILE K < J DO
 BEGIN
  READLN(DFILE);
  K := K + 1;
 END;
 BLKPAGE:
 WRITELN 'FLINT MC MATC NICKNAME FC CDS   COMMENTS');
 J := Ø:
```

```pascal
    WHILE J < 7 DO
    BEGIN
     READ(DFILE,C);
     WRITE(C);
     J := J + 1;
    END;
    READ(DFILE,C);
    WRITE(C)
    READ(DFILE,C);
    WRITE(C,' ');
    J := 0;
    WHILE J < 16 DO
    BEGIN
     READ(DFILE,C);
     WRITE(C);
     J := J + 1;
    END;
    READ(DFILE,C);
    WRITE(C);
    READ(DFILE,C);
    WRITE(C,'  ');
    J := 0;
    WHILE J < 5 DO
    BEGIN
     READ(DFILE,C);
     WRITE(C);
     J := J + 1;
    END;
    J := 0;
    WHILE J < 26 DO
    BEGIN
     READ(DFILE,C);
     WRITE(C);
     J := J + 1;
    END;
    READLN(DFILE);
    WRITELN;
    WRITELN;
    WRITELN('ARE YOU READY TO CONTINUE?  (Y/N)');
    READ(C);
    WHILE C <> 'Y' DO
     READ(C);
   END;

   PROCEDURE LTAB;
   VAR I,SEGL,SEGH: INTEGER;
       DISKL,DISKH: INTEGER;
   BEGIN
    RESET(TABLE,'REFTAB.TEXT');
    READLN(TABLE, DISKL, DISKH);
    IF(RF >= DISKL) AND (RF <= DISKH) THEN
    BEGIN
     READLN(TABLE, SEGL, SEGH, SIZE);
     I := 0;
```

```
  WHILE SIZE <> 999 DO
  BEGIN
   I := I + 1;
   IF(RF >= SEGL) AND (RF <= SEGH) THEN
   BEGIN
    BP := SIZE - 1;
    SIZE := 999;
   END
   ELSE
    BEGIN
     READLN(TABLE,SEGL,SEGH,SIZE);
    END;
  END;
  CASE I OF
   1: SEGMEY := 'SEG1.TEXT';
   2: SEGMEY := 'SEG2.TEXT';
   3: SEGMEY := 'SEG3.TEXT';
   4: SEGMEY := 'SEG4.TEXT';
   5: SEGMEY := 'SEG5.TEXT';
   6: SEGMEY := 'SEG6.TEXT';
   7: SEGMEY := 'SEG7.TEXT';
   8: SEGMEY := 'SEG8.TEXT';
  END;
  RESET(DFILE,SEGMEY);
 END
 ELSE
  BEGIN
   BLKPAGE;
   NFOND;
   WRITELN('DO YOU HAVE ANOTHER DISK?  (Y/N,');
   READ(C);
   CHECK;
   IF C = 'Y' THEN
   BEGIN
    BLKPAGE;
    WRITELN('LOAD THE DISK INTO THE LEFT SIDE DISK');
    WRITELN('DRIVE WITH LABEL FACING YOU AND DOWN.');
    WRITELN;
    WRITELN;
    WRITELN('HAVE YOU DONE THIS?  (Y/N)');
    READ(C);
    WHILE C <> 'Y' DO
     READ(C);
    CLOSE(TABLE,LOCK);
    LTAB;
   END
   ELSE
    EXIT(SEARCH);
  END;
 END;
END;

PROCEDURE LDTAB;
VAR I: INTEGER;
BEGIN
```

51

```
  I := 0;
  WHILE I <= BP DO
  BEGIN
   READ(DFILE,DTAB[I].RFL,DTAB[I].RFH,DTAB[I].PRFL);
   READ(DFILE,DTAB[I].PRFH,DTAB[I].SPL,DTAB[I].SPH);
   READ(C);
   READLN(DTAB[I].ST);
   READLN(DFILE);
   I := I + 1;
  END;
END;

PROCEDURE ENTRY(I:INTEGER);
BEGIN
 CASE I OF
  1: BEGIN
      BLKPAGE;
      WRITELN('ENTER PRF(XXXXX) <rtn>');
      READLN(PRF);
     END;
  2: BEGIN
      BLKPAGE;
      WRITELN('ENTER RF(XXXXX) <rtn>');
      READLN(RF);
     END;
  3: BEGIN
      BLKPAGE;
      WRITELN('ENTER SCAN(XXXX) <rtn>');
      READLN(SCAN);
     END;
  4: BEGIN
      BLKPAGE;
      WRITELN('ENTER TYPE SCAN(AAAAA) <rtn ');
      READLN(SCANTYPE);
     END;
 END;
END;

PROCEDURE HUNT;
BEGIN
  WHILE (TP <= BP) AND (KEEP = TRUE) DO
  BEGIN
   POINT := (BP-TP +1) DIV 2 + TP;
   IF(DTAB[POINT].RFL <= RF) AND (DTAB[POINT].RFH >= RF) THEN
   BEGIN
    GROUPRF(POINT);
    POINT := (BP-TP +1) DIV 2 + TP;
    IF(DTAB[POINT].PRFL <= PRF) AND (DTAB[POINT].PRFH >= PRF)
    THEN
    BEGIN
     GROUPPRF(POINT);
     POINT := (BP - TP + 1) DIV 2 + TP;
     IF(DTAB[POINT].SPL <= SCAN) AND (DTAB[POINT].SPH >= SCAN)
     THEN
```

52

```pascal
        BEGIN
          GROUPSCAN(POINT);
          IF TP <> BP THEN
          BEGIN
            WHILE TP <> BP DO
              BEGIN
                IF (DTAB[TP].ST = SCANTYPE) THEN
                  BEGIN
                    FOUND := TP;
                    KEEP := FALSE;
                  END
                  ELSE
                    TP := TP + 1;
                END;
              END
              ELSE
              BEGIN
                IF DTAB[TP].ST = SCANTYPE THEN
                BEGIN
                  FOUND := TP;
                  KEEP := FALSE;
                END
                ELSE
                  TP := TP + 1;
                END;
    END
    ELSE
    BEGIN
      IF DTAB[POINT].SPL <= SCAN THEN
        TP := POINT
      ELSE
        BP := POINT - 1;
      END;
    END
  ELSE
  BEGIN
    IF DTAB[POINT].PRFL <= PRF THEN
      TP := POINT
    ELSE
      BP := POINT - 1;
    END;
  END
  ELSE
  BEGIN
    IF DTAB[POINT].PFL <= RF THEN
      TP := POINT;
    ELSE
      BP := POINT - 1;
    END;
  END;
END;

BEGIN (* SEARCH *)
  FOUND := 0;
```

53

```
BLKPAGE;
WRITELN('ARE YOU READY TO SEARCH?  (Y/N)');
READ(C);
WHILE C <> 'Y' DO
 READ(C);
ENTRY(1);
ENTRY(2);
ENTRY(3);
ENTRY(4);
KEEP := FALSE;
WHILE KEEP = FALSE DO
BEGIN
 BLKPAGE;
 WRITELN('YOUR ENTRIES ARE:');
 WRITELN;
 WRITELN(' PRF  RF  SCAN  TYPE SCAN');
 WRITELN(PRF,' ',RF, ' ', SCAN, ' ', SCANTYPE);
 WRITELN;
 WRITELN('DO YOU WISH TO CHANGE ANY?  (Y/N)');
 READ(C);
 CHECK;
 IF C = 'Y' THEN
 BEGIN
  WRITELN;
  WRITELN('WHICH ONE DO YOU WANT TO CHANGE');
  WRITELN('(PRF,RF,SCAN,TYPE SCAN) <rtn>');
  READLN(C);
  IF C = 'P' THEN ENTRY(1)
   ELSE
   IF C = 'R' THEN ENTRY(2)
    ELSE
    IF C = 'S' THEN ENTRY(3)
     ELSE
     IF C = 'T' THEN ENTRY(4)
      ELSE
       ERROR;
  END
  ELSE
   KEEP := TRUE;
 END;
LTAB;
LDTAB;
HUNT;
IF KEEP = TRUE THEN
BEGIN
 NFOND;
 WRITELN('ARE YOU READY TO CONTINUE?  (Y/N)');
 READ(C);
 WHILE C <> 'Y' DO
  READ(C);
 END
 ELSE
  FOND;
END;
```

```
.   PROCEDURE TALK

PROCEDURE TALK;
 PROCEDURE CONTINUE;
  BEGIN
   GOTOXY(0,20);
   WRITELN('ARE YOU READY TO CONTINUE? (Y/N)');
   READ(C);
   WHILE C <> 'Y' DO
    READ(C);
  END;

 PROCEDURE PAGE1;
 BEGIN
   BLKPAGE;
   WRITELN('   THE EMITTER IDENTIFIER WORKS BY USING THE ');
   WRITELN('PARAMETERS TAKEN FROM THE CURRENT DETECTION ');
   WRITELN('UNIT.  THE PARAMENTERS ARE THEN ENTERED INTO');
   WRITELN('IDENTIFIER BY THE OPERATOR THROUGH THE KEYBOARD.');
   WRITELN;
   WRITELN('   THE KEYBOARD ENTRIES ARE REQUESTED WHEN THE ');
   WRITELN('OPERATOR HAS RESPONDED TO THE QUESTION, ''ARE YOU');
   WRITELN('READY TO START? (Y/N)''.  THE TWO TYPES OF ENTRIES');
   WRITELN('ARE ONE, A SIMPLE YES OR NO.  TO DO THIS RESPONSE, ');
   WRITELN('MERELY DEPRESS THE KEY LABELED ''Y'' OR ''N'' WHEN ');
   WRITELN('PRESENTED WITH A QUESTION ENDING IN ''Y/N).');
   CONTINUE;
 END;

 PROCEDURE PAGE2;
 BEGIN
   BLKPAGE;
   WRITELN('   THE OTHER TYPE OF RESPONSE IS FOLLOWED BY DE-');
   WRITELN('PRESSING THE KEY LABELED ''RETURN''. LIKE THESE:');
   WRITELN;
   WRITELN('     ENTER PRF(XXXXX) <rtn>         ');
   WRITELN('     ENTER  RF(XXXXX) <rtn>         ');
   WRITELN('     ENTER SCAN(XXXXX) <rtn>        ');
   WRITELN('     ENTER SCAN TYPE(AAAAA) <rtn>   ');
   WRITELN;
   WRITELN('FIRST, THE X''S REPRESENT NUMBERS AND THE A''S RE-');
   WRITELN('PRESENT CHARACTERS.  THE NUMBER OF X''S OR A''S');
   WRITELN('REPRESENT THE MAXIMUM NUMBER OF POSITIONS ALLOWED');
   WRITELN('IN THE RESPONSE.  SIMPLY ENTER EXCATLY WHAT IS ');
   WRITELN('DISPLAYED ON THE CURRENT DETECTION UNIT, FOLLOWED');
   WRITELN('BY THE RETURN <rtn> KEY. ');
   CONTINUE;
 END;

 PROCEDURE PAGE3;
 BEGIN
   BLKPAGE;
   WRITELN('   IF YOU HAVE MADE A MISTAKE IN THE ENTRY, BEFORE');
   WRITELN('DEPRESSING THE RETURN KEY, ALL YOU HAVE TO DO IS ');
```

```
  WRITELN('TO DEPRESS THE KEY LABELED WITH A LEFT POINTING ');
  WRITELN('ARROW ON IT.  THEN MAKE THE CORRECT RESPONSE. ');
  WRITELN('IF, HOWEVER, YOU DID PRESS THE RETURN KEY, YOU');
  WRITELN('WILL BE ABLE TO CORRECT IT AT THE VERIFICATION.');
  CONTINUE;
END;

PROCEDURE PAGE4;
BEGIN
  BLKPAGE;
  WRITELN('TO VERIFY YOUR ENTRIES THE FOLLOWING MESSAGE APPEARS:');
  WRITELN;
  WWRITELN('     YOUR ENTRIES ARE:    ');
  WRITELN;
  WRITELN('    PRF      RF      SCAN      SCAN TYPE ');
  WRITELN('  XXXXX    XXXXX      XXXXX       AAAAA   ');
  WRITELN;
  WRITELN('DO YOU WANT TO CHANGE ANY?  (Y/N) ');
  WRITELN;
  WRITELN('IF YOU RESPOND YES.  THE FOLLOWING MESSAGE APPEARS: ');
  WRITELN;
  WRITE('WHICH ONE DO YOU WANT TO CHANGE');
  WRITELN(' PRF,RF,SCAN,TYPE SCAN)?  <rtn> ');
  WRITELN;
  WRITELN('YOU SIMPLY ENTER EITHER PRF, OR RF, OR SCAN, ');
  WRITELN('OR TYPE SCAN FOLLOWED BY THE RETURN KEY.  THE');
  WRITELN('IDENTIFIER WILL AGAIN ASK FOR THAT ENTRY. ');
  CONTINUE;
END;

PROCEDURE PAGE5;
BEGIN
  BLKPAGE;
  WRITELN('   THE OUTPUT OF THE IDENTIFIER IS ONE OF THE ');
  WRITELN('TWO FOLLOWING FORMS:');
  WRITELN;
  WRITELN('ELINT   MC  NATO NICKNAME  EC  CDS NR.   COMMENTS');
  WRITELN('AAAAA   X    AAAAAAAAAAA    AA    XXXX      AAAAAAAA');
  WRITELN('AAAAA   X    AAAAAAAAAAA    AA    XXXX      AAAAAAAA');
  WRITELN;
  WRITELN('                         OR                       ');
  WRITELN;
  WRITELN('    PRF        RF        SCAN       SCAN TYPE ');
  WRITELN('   XXXXX     XXXXX      XXXXX        AAAAA ');
  WRITELN('NOT FOUND');
  CONTINUE;
END;
```

```
EGIN   (* START OF PROCEDURE TALK  *)
  PAGE1;
  PAGE2;
  PAGE3;
  PAGE4;
  PAGE5;
ND;   (* END OF PROCEDURE TALK  *)
```

E. MAIN PROGRAM

```pascal
PROGRAM ID;
VAR    C: CHAR;
     LOOP: BOOLEAN;

PROCEDURE ERROR;
  BEGIN
   WRITELN;
   WRITELN('INCORRECT RESPONSE');
   WRITELN('PLEASE, TRY AGAIN');
   READ(C);
   END;

PROCEDURE CHECK;
  BEGIN
   WHILE C<>'Y' AND C<> 'N' DO
    ERROR;
   END;

PROCEDURE BLKPAGE;
VAR CNT: INTEGER:
  BEGIN
   CNT:= 0;
   WHILE CNT < 26 DO
    BEGIN
     WRITELN;
     CNT:= CNT + 1;
    END;
   GOTOXY(0.0);
   END;

PROCEDURE TALK;
(SEE APPENDIX B ITEM D)

PROCEDURE REMAT;
(SEE APPENDIX B ITEM A)

PROCEDURE SORT;
(SEE APPENDIX B ITEM B)

PROCEDURE SEARCH;
(SEE APPENDIX B ITEM C)

BEGIN  (* MAIN PROGRAM *)
  LOOP := TRUE;
  BLKPAGE;
  WRITELN('WELCOME TO THE ELECTRONIC EMITTER IDENTIFIER.');
  WRITELN;
  WRITELN('HAVE YOU USED ME BEFORE?  (Y/N) ');
  READ(C);
  CHECK;
  IF C = 'N' THEN TALK
   ELSE
```

```
      BEGIN
        BLKPAGE;
        WRITELN('DO YOU NEED A REFRESHER?   (Y/N) ');
        READ(C);
        CHECK;
        IF C = 'Y' THEN TALK;
      END;
    BLKPAGE;
    WRITELN('DO YOU HAVE A DISK LABELED DATA?  (Y/N) ');
    READ(C);
    CHECK;
    IF C = 'Y' THEN SEARCH
     ELSE
      BEGIN
       REMAT;
       SORT;
      END;
    WHILE LOOP = TRUE DO
      SEARCH;
END.   (* MAIN PROGRAM  *)
```

BIBLIOGRAPHY

1. Naval Electronic Engineering Office Damneck, _Command Presentation_, 1979.

2. Bush, R.F.J., "Soviet ESM Capabilities Detailed", _Electronic Warfare and Defense Electronics_, Dec. 1978, 60-68.

3. Fawcett, Dr. C.W., "Passive Warfare for Destroyers", _Navsea Journal_, Mar. 1977, 24-29.

4. Hartman, R., "EW Essentials for FPB's", _Electronic Warfare and Defense Electronics_, Jan. 1979, 55-67.

5. Fatch, B., "Computer Use in Electronic Warfare", _Microwave Journal_, Sept. 1978, 53-62.

6. Hellerman, H., _Digitial Computer System Principles_, McGraw-Hill, 1973.

7. Horowitz, E. and Sahni, S., _Fundamentals of Computer Algorithms_, Computer Science Press, Inc., 1978.

8. Institute for Information Systems, _UCSD (Mini-Micro Computer) PASCAL Reference Manual_, 1978.

9. Smith, S.W., _Operational EA-6B Mission Planning Programs_, Master's Thesis, Naval Postgraduate School, 1978.

10. Godley, J.R., _Microcomputer Based Generator of Recurring Operational Reports_, Master's Thesis, Naval Postgraduate School, 1977.

DISTRIBUTION LIST

No. Copies

1. Defense Documentation Center
   Cameron Station
   Alexandria, Virgina 22314   2

2. Library, Code 0142
   Naval Postgaduate School
   Monterey, California 93940   2

3. Professor Grodon H. Bradley, Code 52Bz
   Department of Computer Technology
   Naval Postgraduate School
   Monterey, California 93940   1

4. LCDR Frank Burkhead, Code 523g
   Department of Computer Technology
   Naval Postgraduate School
   Monterey, California 93940   1

5. Lt. Gary L. Bush
   924 North Dixon Street
   Gainesville, Texas 76240   1

6. Professor N.F. Schneidewind, Code 52Ss
   Department of Computer Technology
   Naval Postgraduate School
   Monterey, California 93940   1